

SRE 4S Ambulance- SS Sretcher



SKYY RIDER



Specification :

MOTOR & TRANSMISSION	
MOTOR	2000 WATT 48 V
CONTROLLER	INTELLIGENT TYPE
CONVERTER	48V DC TO AC
DRIVE TYPE	AUTOMATIC
MOTOR TYPE	PMSM TYPE
MAX RPM	3000 RPM
MAX TORQUE (NM)	28 NM
GEAR BOX	REDUCTION TYPE
TRANSMISSION TYPE	DIRECT DRIVE

FUEL & PERFORMANCE	
Fuel Type	Electric
Mileage (City)	50-60 km
Max Speed	30 kmph
Passenger Capacity	4 + Strecher
Battery Type	Lead acid / Lithium ion
Charging Time	7-8 Hr (For lead acid)
Charging Time	3-4 Hr for lithium ion

SUSPENSION,BODY, STEERING & BRAKES	
FRONT SUSPENSION	LEAF SPRING WITH GAS CHARGED TELESCOPIC SHOCKERS
REAR SUSPENSION	4.5 MM X 5MM LEAP SPRING WITH ADD. COIL
TYRE SIZE	165-60-12
TYRE TYPE	6 PLY TUBELESS
RIM SIZE	12 INCH
PARKING BRAKE	MECHANICAL LINKAGE TYPE
STEERING	RACK AND PINION TYPE
REAR NBRAKE TYPE	HYDRULIC DRUM

OTHERS	
Fuel Type	Electric
Roof	FRP
Operating Switches	Steering Control Combination Switch
Body Color	Powder Coated Chasis
Headlight	Filament
Bottle Holder	Yes
Reverse Buzzer	With Buzzer/Without(As Per Needs)
Flooring	3mm Insulated,Electric Shock resistance
Steering	Ultra Finish Golf Steering
Dimension	3505 X 1220 x 1920

Standard Accesories :

Outside Rear view mirrors, Side Indicator, Head Lights, Tail lights, fire extinguisher ,Emergency stop button, Tool kit, Jack,Operational Manual,Roof handles, Reverse buzzer,Horn , Spare key

Optional Accesories :

Rain Cover , Dust cover